

PURCHASING DEPARTMENT

Madison County Board of Supervisors 146 West Center Street Canton, MS 39046 / 601-855-5534 kesha.jackson@madison-co.com

February 7, 2022

To:

Board of Supervisors

From:

Kesha Jackson, Purchasing Clerk

Subject:

Award Hydraulic Diesel Excavator & Tractor - Road Department

Attached are copies of the results of the recent reverse auction for a Hydraulic Diesel Excavator & Tractor.

I recommend that the Board take the following actions:

- 1. Acknowledge bids received;
- 2. Award Hydraulic Diesel Excavator to TraxPlus as the lowest and best bidder
- 3. Award Tractor to Stribling Equipment as the lowest and best bidder

Thank you in advance for your consideration of the above recommendations.

Menu

Create New Bid View Pending Bids View Open Bids View Closed Bids

View Public Log Bid System Log Permissions

Excavator

Current Time: 01-25-2022 11:03:31

am

s Planning and Zoning Bid Tool Email Manager Help Bid Tool

Show 10 ✓ entries

Search:

ID	Name	Phone	Email	Company Name	Date Submitted	Bid Amount	View Bid
2575	Casey Echols	(601) 906- 8568	casey@traxplus.com	TraxPlus	01-25-2022 10:09:49 am	\$195,000.00	
2576	Brad Butler	(601) 939- 4000	bbutler@lylemachinery.com	Lyle Machinery Company	01-25-2022 10:12:11 am	\$226,000.00	
2579	Brandon Martin	(601) 573- 8855	brandon.martin@striblingequipment.com	Stribling Equipment	01-25-2022 10:44:41 am	\$218,500.00	

Showing 1 to 3 of 3 entries

Previous 1 Next

MADISON COUNTY, MISSISSIPPI INVITATION FOR BIDS Hydraulic Diesel Excavator and Tractor

The Madison County Board of Supervisors will receive un-priced proposals on the following:

- 1. Hydraulic Diesel Excavator
- 2. Tractor

Un-priced proposals will be accepted until 10:00 a.m. on Thursday, January 20, 2022 by electronic submission at http://www.madison-co.com/bids or in a sealed envelope at the Chancery Clerk's Office, 125 West North Street, Canton, Mississippi. For any questions relating to the electronic submission process, please call Kesha Jackson at 601-855-5534.

Submitted un-priced proposals will be evaluated, and vendors submitting acceptable proposals will be invited to submit priced bids. Bidding will be held by electronic reverse auction on Tuesday, January 25, 2022, at 10:00 a.m. Bidders may come to the Office of Purchasing with a paper bid and receive technical assistance in entering their bid in the reverse auction.

Specifications for the Hydraulic Diesel Excavator and Tractor are available on the bid page of the Madison County Board of Supervisors at: http://www.madison-co.com/bids. Additionally, specifications are on file in the Chancery Clerk's Office, Madison County Office Complex, 125 West North Street, Canton, Mississippi, 39046 and available during normal business hours. There is no charge for specifications obtained using either of these methods.

All bids must comply with the specifications provided. Madison County reserves the right to amend the specifications, as necessary, and agrees to notify all who have requested bid packets from the Madison County Board of Supervisors.

The Madison County Board of Supervisors reserves the right to extend the auction date if necessary, to complete the bid proposal pre-qualification process.

Electronic proposals must be submitted at http://www.madison-co.com/bids.

All in-person submitted un-priced proposals must be sealed and clearly labeled on the outside of the bid envelope as instructed in the bid package and delivered to the Chancery Clerk's Office, at 125 West North Street, Canton, Mississippi.

The Board of Supervisors reserves the right to reject any and all bids.

SUBMITTED: MADISON COUNTY JOURNAL

FOR PUBLICATION ON: Thursday, December 23, 2021

Thursday, December 30, 2021

PROOF OF PUBLICATION TO: Madison County Chancery Clerk

PO Box 404

Canton, MS 39046

Trax Plus

Required Specifications for Madison County, Mississippi Board of Supervisor

One or More:

2022 Model Year Hydraulic Diesel Excavator

HYDRAULIC EXCAVATOR SPECIFICATIONS

YXN	Engine net	powershall	beatleast	160 hp
-----	------------	------------	-----------	--------

- YxN Minimum operating weight up to 49000lbs.
- YxN Digging depth shall not be less than 216'
- YxN Reachatground level shall not be less than 32'
- YXN Transport width shall not be over 10'5"
- YxN Engine shall have an electric fuel priming pump
- Yx N Engine shall run on either low-sulfur diesel or biodiesel
- YXN Engine shall have a minimum of 4.4L displacement
- Y_N_x Maximum travel speed shall be at least 3.5 mph 3.3 mph Maximum travel speed
- Y_XN _Machine to be equipped with auxiliary hydraulics, single and double function
- Y Nx Machine shall have automatic 2 speed travel Low and High speed
- YxN_Undercarriage length shall be at least 14'6'
- Y_N_X Machine shall be equipped with rear and side cameras Rear-facing camera
- YXN_ Machine to be equipped with pattern control changer
- YXN Machineshall be equipped with a reach boom not less than 18'8"
- YxN Swing torque shall be at least 54000 lb.ft.
- Yx N Overall height at least 10'
- Y_NxSwing speedshallbeatleast11rpm 10.9 rpm
- YxN Machine shall have sealed and lubricated track rollers, carrier rollers and idlers
- Y_X N_Fuel tank will have a minimum of 84 gallons
- YX N_Hydraulic thumb minimum 48" 1.8 cubic yard bucket

5 Year/5,000hr Warranty Included

Search:

Home Administrators Site Members Page Creator Hit Statistics Agenda Builder Planning and Zoning Archives

Show 10 ✓ entries

Menu

s Planning and Zoning Bid Tool Email Manager Help Bid Tool

Create New Bid

View Pending Bids View Open Bids

View Closed Bids View Public Log Bid System Log Permissions

Dozer Tractor

Current Time: 01-25-2022 11:04:09

am

ίD	Name	Phone	Email	Company Name	Date Submitted	Bid Amount	View Bid
,	Brandon Martin	(601) 573- 8855	brandon.martin@striblingequipment.com	Stribling Equipment	01-25-2022 10:23:31 am	\$295,873.00	
	Brandon Martin	(601) 573- 8855	brandon.martin@striblingequipment.com	Stribling Equipment	01-25-2022 10:23:31 am	\$295,873.00	

Showing 1 to 2 of 2 entries

Previous 1 Next

Switch to Advanced View

Required Specifications for Madison County, Mississippi Board of Supervisors

One or More: 2022 Track-Type Tractor

South Deals 750 L



TRACK-TYPE TRACTOR SPECIFICATIONS

Y_N_Engine net power shall be at least 18hp 6 cylinder diesel

Y_N_Minimum operating weight 42000 lbs. HI, 500

Y_N_Engine air cleaner shall have an electronic service indicator

Y_N_Machine shall be equipped with a 24 volt electrical system

Y_N_Engine shall be equipped with an electric fuel priming pump

Y_N_Transmission shall have maximum forward speed of 6 mph

Y_N_Transmission shall have a maximum reverse speed of 7.5 mph

Y_N_Machine to have a 6 way dozer blade with 24 degree angle left or right

Y_N_Minimum blade width of 13', Height 40 inches

Y_N_Blade capacity minimum 4.0 cubic meters

YAN Undercarriage track length on ground shall be a minimum of 10 feet 1 inch

Machine to be factory installed integrated GPS or beer grading systems adaptable.

 $\begin{picture}(20,0)\put(0,0){\line(0,0){100}} \put(0,0){\line(0,0){100}} \put(0,0){\line(0,0){100}$

JOHN DEERE 210 G

		JOHN DEERE	
		210 G	
DESCRIPTION		T4 SIV	
		CANADA, USA	
Dipper Length - Standard It/in	50.005.04 8 8 9 0 0 8 8 4 4 5 5 5 4 4 4 5 5 5 6 5 6 5 6 5 6 5 6	9 ft 7 in	
Telematics Available		✓	

	JOHN DEERE
	210 G
DRIVELINE	Ta SIV
	CANADA USA
Emission Rating	Tier 4
Engine Manufacturer	John Deere Power Tech
Engine Model	Power Tech PVS
Aspiration	Variable-Geometry Turbocharger (VGT)
Displacement Inches	415
Rated Speed rpm	2000
Engine Output - Net hp	159
Number Of Track Rollers - Each Side	7
Track Shoe Width inches	32

DIMENSIONS	JOHN DEERE 210 G T4 SIV CANADA USA
Transport Length Mono Boom ft/in	31 ft 3 in
Transport Height - Maximum (vin	9 ft 11 in
Overall Undercarriage Width ft/in	9 ft 11 in
Track Length On Ground tr/in	11 ft
Zero Tailswing	×
Ground Clearance inches	17.72
Capacity Standard	SAE
Heaped Bucket Capacity - Standard yd*	1.19
Bucket Weight - Standard lbs	2035
Nidth Over Fixed Tracks (trin	9 ft 11 in
Digging Reach - Mono Boom t/Jin	32 ft 7 in
Ground Level Reach - Mono Boom fr/in	32 ft
Dig Height - Mono Boom tVin	32 ft 11 in
Dump Height - Mono Boom fr/in	23 ft 7 in
/ertical Wall - Mono Boom tulin	19 ft 8 in
Dig Depth - Mono Boom (Vin	21 ft 11 in

		JOHN DEERE	
		210 G	
CAPACITIES		T4 SIV	
		CANADA, USA	
Fuel Tank gallons (US)	ASSESSMENT AND ASSESSMENT ASSESSM	106.5	
Hydraulic Tank gallons (US)	2	35.7	

	JOHN DEERE
REDEORMANOE	210 G
PERFORMANCE	Ta SIV
	CANADA, USA
Ground Bearing Pressure PSI	5.47
Dipper Tearout lbf	25628
Bucket Breakout lbf	35520
Total Flow gallons (US) / min	112
Boom Pressure PSI	4975

	JOHN DEERE	
WEIGHTO	210 G	
WEIGHTS	7d SIV	
	CANADA, USA	
Operating Weight lbs	51061	

35 attributes



Powered by Spec Check www.speccheck.com

JOHN DEERE 750 L LGP

DESCRIPTION

Undercarriage Type

Cab - Type Rops Fops

Traction Control System

Rear View System Available

JOHN DEERE 750 L LGP



USA CANADA

LGP



Cab



Option

Rear View Camera



JDLink

Option

Smart Grade

Telematics Available Platform Grade Control Available

Platform

Platform

DRIVELINE

JOHN DEERE

750 L LGP





USA CANADA John Deere

PowerTech PVS 6068

EPA Tier 4 / EU Stage V

Turbo - Charge Air Cooled

414

1700

175

Hydrostatic

Infinitely Variable

2

8

No - Inline

7.5

34

Single Grouser - Moderate Service

9048

45

Hydrostatic

Engine Manufacturer

Engine Model

Emission Rating

Aspiration

Displacement Inches

Rated Speed rpm

Engine Output - Net hp

Transmission Type

Speed Mode - 1

Carrier Rollers

Track Rollers Raised Sprocket

Shoe - Pitch inches

Shoe - Width inches

Shoe - Type

Ground Contact Area Inches

Number Of Shoes

Service Brake Type

DIMENSIONS

JOHN DEERE

750 L LGP



USA, GANADA

Height - Max fuin		11 ft 6 in
Height - Top Of Rops (t/in		10 ft 8 in
Ground Clearance inches		14
Width - Over Tracks ft/in		9 ft 10 in
Track Length - On Ground ft/in		10 ft 2 in
Blade		PAT
Blade - Width ft/in		13 ft
Blade - Height fuin	2	4 ft 8 in
Blade - Dig Depth inches		25.5
Blade - Lift Clearance ft/in		3 ft
Blade - Tilt fuin		1 ft 8 in
	1.00	

			JOHN DEERE	
			750 L LGP	
CAPACITIES			Ta sv	
			USA, CANADA	
Fuel Tank gallons (US)	SATISFACTOR OF STREET,	CONTRACTOR DESCRIPTION OF THE CONTRACTOR OF THE	97.7	
Blade - Capacity yda			5.9	

	JOHN DEERE
	750 L LGP
PERFORMANCE	T4 SV
	USA CANADA
Speed - Forward Maximum mph	6
Speed - Reverse Maximum mph	6
Ground Bearing Pressure PSI	4.42
Implement Pump - Flow gallons (US) / min	34
Implement Pump - Pressure PSI	3625

	JOHN DI	ERE
WEIGHTO	750 L I	.GP
WEIGHTS	TO 1	v i de la companya de
	USA CAI	
Operating Weight lbs	3997	6

48 attributes



Powered by Spec Check www.speccheck.com