### **BOARD OF SUPERVISORS**

#### **MADISON COUNTY, MISSISSIPPI**

Department of Engineering Tim Bryan, P.E., PTOE, County Engineer 3137 South Liberty Street, Canton, MS 39046 Office (601) 855-5582 FAX (601) 859-5857

#### **MEMORANDUM**

November 17, 2025

To: Casey Brannon, Supervisor, District I Trey Baxter, Supervisor, District II Gerald Steen, Supervisor, District III Karl Banks, Supervisor, District IV Paul Griffin, Supervisor, District V

From: Tim Bryan, P.E., PTOE County Engineer

Re: Telepak Networks/D.B.A. Cspire Utility Permit County Road Name, Glenwild Circle

The Engineering Department recommends approval for Cspire to do construction of underground fiber-optic internet utility, by method of directional bore, within the right of way county-maintained roads listed below.

- Glenwild Circle/Azure Drive
- Aurora Circle

Revised: 2/14/2019



# PERMIT APPLICATION FOR THE CONSTRUCTION OR ADJUSTMENT OF A UTILITY WITHIN COUNTY ROAD RIGHT-OF-WAY

<u> Utility Information:</u>	Utility Name:			
Address:			City/State/Zip:	
Contact Person:			Contact's Phone:	
Project Information:	County Road Name:			se Appendix 1 for additional descriptions)
Beginning Location:		Enc	ing Location:	
Length of Project:	Sec	ction:	Township:	Range:
Description of Work: _				
Check Box if Appendi	x 1 is to be included as a	part of this App	lication	

Whereas the above stated Utility makes application to the **Madison County Board of Supervisors** for a Construction Permit. Attached hereto are drawings and plans for the construction of the above facilities located within Madison County owned public rights-of-way. Once stamped by the Madison County Engineering Department, these plans shall not be changed or altered without written approval of the County Engineer, or his representative. A copy of the approved permit and plans shall be on-site at all times during construction.

The Applicant Utility shall comply with all policies, procedures and construction practices as outlined in *A Policy for The Accommodation of Utility Facilities within the Right-of-Way of all Public County Roads* (hereinafter referred to as the "Policy"), as adopted on November 1, 2005, by the **Madison County Board of Supervisors**, and which is hereby made a part of this Application Agreement.

If facilities are to be located within the Rights-of-Way of the County-Federal or State Aid System, Applicant Utility also agrees to comply with applicable provisions of *S.O.P. No. SA II-2-8, Accommodation of Utilities on Rights-of-Way,* issued by the State Aid Engineer and dated July 1, 2005.

The Applicant Utility understands and agrees that, except as herein granted, no right, title, claim, or easement to said road right-of-way is granted by the issuance of this permit. If this Utility is listed in the general provisions of the Policy, it will be adjusted to comply with same without cost to the County, unless the variance from the Policy has been approved by the granting of the Permit pursuant to this Application.

The Applicant Utility further understands that the Utility's engineering, plant, or other personnel will be responsible for the staking and construction supervision of the work set out above and as shown on the attached plans. If work impacts traffic in any way, the appropriate traffic control shall be installed per the *Manual of Uniform Traffic Control Devices*, Latest Edition.

The Applicant Utility understands that the County Engineer, or his representative, may issue a Stop Work Order at any time if it is deemed that site conditions are not suitable for construction or if any of the requirements of this permit are not being met.

Many County Roads have variable Rights-of-Way and/or no Right-of-Way at all and are maintained under a Prescriptive Easement. It is the sole responsibility of the Applicant Utility to verify the existence and limits of public rights-of-way. If none exists, it is the

responsibility of the Applicant Utility to acquire an easement for their Facilities from the applicable property owner(s). Madison County in no way verifies the limits of Right-of-Way as shown on the permit application.

The Applicant Utility shall be responsible for all future maintenance and repair of the facilities installed under this permit. The Applicant Utility shall make future adjustments to, or relocate, the facilities located within road or highway right-of-way when required for road or highway widening or other road or highway construction at no cost to Madison County. The Applicant Utility shall relocate said utilities within sixty (60) days of notification by County by registered mail, return receipt requested, unless otherwise designated by the County Engineer. Further, any maintenance, repair, or construction shall be done in such a manner as to occasion no unreasonable interference with the normal flow and safety to traffic and at the expense of the utility company. When reasonable care has been taken to locate said utility facilities within the right-of-way, the Applicant Utility understands that any damages caused by routine maintenance and construction by County forces shall be borne by the Applicant Utility.

The Applicant Utility further agrees to indemnify and hold Madison County harmless for any and all claims, accidents, damages, liabilities and expenses occasioned wholly, or in part, by any act or omission of applicant, its agents or employees. In case County shall, without fault on its own part, be made a party to any litigation commenced by or against applicant, then applicant shall protect and hold County harmless, and shall pay all costs, expenses and reasonable attorney's fees incurred or paid by County in connection with said litigation.

day of

All underground facilities shall be installed at a depth equal to or greater than 48" below the lowest adjacent grade.

All pipes carrying liquid shall be encased under County maintained roads.

WITNESS the signature of the Applicant this the

		Ву:	(Appligant Signature)
		Title:	
Note:	Applicant must be an employee of the Utility named in this ap a Contractor, Subcontractor, Agent, or Consulting Engineer as performed under this application.	•	, , ,
plans s	my authorized representative, have reviewed this ap submitted by the Applicant meet the requirements or the county for the state of May of all Public County Boards.	•	
_	ight-of-Way of all Public County Roads.  B" MIN DOC REQUIRED AT ALL LOCATIONS	APP	ROVED
	N MADISON COUNTY RIGHT OF WAY	By Tir	m Bryan at 9:06 am, Nov 26, 2025
			Tim Bryan, P.E. County Engineer
AGREE	ED TO AND APPROVED BY:		
			Date:
	Madison County Board President		
ENTER	RED INTO THE MINUTES OF THE BOARD OF SUP	ERVISORS O	F MADISON COUNTY, MISSISSIPPI ON THIS
	, 20,	·	


# Appendix 1

County Road Name:			
Beginning Location:		Ending Location:	
Length of Project:	Section:	Township:	Range:
Description of Work:			
County Road Name:			
Beginning Location:		Ending Location:	
Length of Project:	Section:	Township:	Range:
Description of Work:			
County Road Name:			
Beginning Location:		Ending Location:	
Length of Project:	Section:	Township:	Range:
Description of Work:			
County Road Name:			
Beginning Location:		Ending Location:	
Length of Project:	Section:	Township:	Range:
Description of Work:			
County Road Name:			
Beginning Location:		Ending Location:	
Length of Project:	Section:	Township:	Range:
Description of Work			



# **GLENWILD 3**

**CITY OF CANTON** MADISON COUNTY, MISSISSIPPI 10/24/2025



## PERMITS REQUIRED

CITY:

N/A

COUNTY:

YES

MDOT:

N/A

FEDERAL:

N/A N/A

RAILROAD: PRIVATE R/W: N/A

N/A

MISC:

LOTS PER MILE

**MILEAGE** 

**HOUSE COUNT** 

163

163

2.29

71.18

0

OCCUPIED:


VACANT:

TOTAL:

PREPARED BY:




DUCT	DETAIL LEGEND
1	BLUE DUCT
2	ORANGE DUCT
3	GREEN DUCT
4	BROWN DUCT






MADISON COUNTY, MISSISSIPPI


# **FLOWER POT** (9.5x12)




# **UH-2.5** (13x24x18)



# **UH-3** (24x36x24)




### TYPICAL VAULT HAND HOLE INSTALLATION PROCEDURES AT BUILDING ENTRIES



VAULT INSTALLATION LOCATION WILL BE MARKED BY A STAKE AND/OR PAINT. CSPIRE/ OSP WILL INSTALL CONDUIT 8" UNDERGROUND TO DESIRABLE VAULT LOCATION

#### TYPICAL VAULT INSTALLATION



PIGTAILS ARE TO BE INSTALLED AT TEST STATION (T.S.) ONLY.

1. THIS ASSEMBLY IS RATED FOR A STATIC DESIGN LOAD OF 15,000 LBS. [66,720 N] OVER A 10 [254] X 10 [254] AREA AND MUST PASS A MIN. STATIC TEST LOAD OF 20,00 LBS.

2 ALL ENGLOSURES BOXES AND COVERS ARE REQUIRED. TO CONFORM TO ALL TEST PROVISIONS OF ANSI/SCTE 77 2007 "SPECIFICATION FOR UNDERGROUND ENCLOSURE INTEGRITY" AS MANUFACTURED BY QUAZITE OR **EQUIVALENT WITH TELEPAK NETWORK'S ENGINEER'S** SIGNED APPROVAL. THE COVERS MUST BE RATED FOR TIER 15 APPLICATIONS AND BOXES RATED FOR TIER 22 APPLICATIONS AND IN NO ASSEMBLY CAN THE COVER DESIGN LOAD EXCEED THE DESIGN LOAD OF THE BOX. ALL COMPONENTS IN AN ASSEMBLY (BOX & COVER) ARE MANUFACTURED USING MATCHED SURFACE TOOLING, ALL COVERS ARE REQUIRED TO HAVE A MINIMUM COEFFICIENT OF FRICTION OF 0.50 IN ACCORDANCE WITH ASTM C 1028 AND HAVE TIER 15 AND "TELEPAK NETWORKS 800-342-3716" EMBOSSED ON THE TOP SURFACE. ALL COVER BOLTS TO BE SELF-CLEANING AUGER BOLT

DIMENSIONS ARE IN INCHES OR MILLIMETERS IN BRACKETS UNLESS OTHERWISE NOTED.

HANDHOLES ARE TO BE INSTALLED A MINIMUM OF THREE FEET

FROM ANY UTILITY OR POWER POLE.

VAULT 24x36x24

VAULT 13x24x18

DESCRIPTION

VAULT (ROUND) 9.5x12

**BOXES** (Nestable)

48" MIN DOC REQUIRED IN ALL LOCATIONS ON MADISON COUNTY ROW

DESIGN/TEST

LOAD#


20.000 LBS

20.000 LBS

20,000 LBS

ALL CABLE WILL BE PLACED BY METHOD OF DIRECTIONAL BORE MIN 2' OFF ROW OR EASEMEN' @ 42" DOC UNLESS OTHERWISE NOTED

NOTIFY ALL UTILITIES 72 HOURS PRIOR TO CONSTRUCTION ACTIVITY. ONE CALL SYSTEM @ 1-800-227-6477



# PREPARED BY Delta Fiber

JOB DESCRIPTION

GLENWILD 3

CANTON

MATERIALS LIST

1 MINI OTE 2 PORT 2 MINI OTE 4 PORT

3 MINI OTE 8 PORT

8 24 CT MICRO LOOP

9 24 CT MICRO TAIL

11 48 CT MICRO LOOP 12 48 CT MICRO TAIL 13 72 CT MICRO 14 72 CT MICRO LOOP

15 72 CT MICRO TAIL 16 96 CT MICRO 17 96 CT MICRO LOOP 18 96 CT MICRO TAIL 19 144 CT MICRO 20 144 CT MICRO LOOP 21 144 CT MICRO TAIL 22 144 CT MICRO FEEDER

144CT M/FEEDER LOOP 24 144CT M/FEEDER TAIL 25 288 CT MICRO 26 288 CT MICRO LOOP 27 288 CT MICRO TAIL

28 288 CT MICRO FEEDER 29 288 CT M/FEEDER LOOP

30 288 CT M/FEEDER TAIL

31 BDO144P LCP

32 BDO288P LCP

33 BDO432P LCP

34 BDO576P LCP

35 FLOWER POT

37 UH2.5 W/22k LID

41 1-1.00" SDR11 HDPE 42 2-1.00" SDR11 HDPE 43 3-1.00" SDR11 HDPE

49 TYCO "D" SPLICE CASE

MAP NUMBER

44 1-18/14-2 WAY

45 1-18/14-4 WAY 46 EXISTING PIPE 47 TYCO "A" SPLICE CASE 48 TYCO "B" SPLICE CASE

50 GROUND ROD

51 OTE SPLICES

52 NON-OTE SPLICES 53 BM53FA

36 UH2.5

38 UH3

39 UH4

40 UH5

10 48 CT MICRO

5 12 CT FOC LOOF 6 12 CT FOC TAIL 7 24 CT MICRO

4 12 CT FOC

DESCRIPTION QTY.

DESCRIPTION CONSTRUCTION

DELTA FIBER

PROJECT NAME

PROJECT CITY

SHEET TYPICALS

PREPARED FOR



MADISON COUNTY, MISSISSIPPI

# SYMBOLS KEY

						PROPERTY LINE	
DIRECTIONAL BORE	—— DB——	RAILROAD TRACKS				EDGE OF PAVEMENT	—EOP———EOP—
AERIAL CABLE		AUXILLARY TRACKS		50' 🗕 ⊨	1 1 1	BACK OF CURB	—BOC——BOC—
PLOW OR BURIED CABLE				<del></del>	<del></del>	WHITE LINE	—
		CENTERLINE		<del></del>		RIGHT-OF-WAY LINE	
DIRECTIONAL BORE 5" HDPE	DB	WOOD LINE			·- <del></del>		
PVC OR SPLIT PVC CONDUIT		DITCH LINE			·- <u>-</u> -	TAX DISTRICT BOUNDARY	T038-42 51762A
ASTMA 139 GRADE B STEEL		TOP OF SLOPE		TOP OF SLOPE			31702A
JACK AND BORE		TOE OF SLOPE					<b>42</b> ">
CORE BORE				TOE OF SLOPE		PROBE (DEPTH AS INDACATED)	
		AERIAL UTILITY (ELECTRIC)		——— E —	(15")		P.T.F.
EXISTING TELEPAK CABLE		UNDERGROUND UTILITY (TELEF (PARTIAL CAPSULE INDICATES (	PHONE) COVER DEPTH IN INCHES)	TEL	(.5)	PERMIT TRACKING FORM IDENTIFIER	187
HANDHOLE		CAUTION NOTES		CAUTION CAUTION GAS X-ING GAS X-ING	CAUTION WATER X-ING		
HANDHOLE (CABLE IN HDPE)		WATER VALVE		Ø×	1		
HH (CABLE IN PVC CONDUIT)		WATER METER		⊞		DELTA FIBER TYPI	CAL LINETYPES
		GAS VALVE		$\Diamond$		1-1.00 HDPE (1)1.00 HDPE (1)1.00 HDPE	(1)1.00 HDPE(1)1.00 HDPE(1)1.00 HDPE
HANDHOLE (CABLE IN GSP CONDUIT)	<del></del>	FIRE HYDRANT		-\$		2-1.00 HDPE (2)1.00 HDPE (2)1.00 HDPE	-(2)1.00 HDPE(2)1.00 HDPE(2)1.00 HDPE
FLOWER POT				ı		3-1.00 HDPE (3)1.00 HDPE (3)1.00 HDPE (3)1.00 HDPE	
	H	STORM DRAIN				18/14 4 WAY — 18/14 4 WAY — 18/14 4 WAY — 18/14 2 WAY — 18	
MANHOLE (CABLE IN HDPE)	<u> </u>	SEWER MANHOLE		S		EXIST PIPE — EXIST PIPE — EXIST PIPE —	EXIST PIPE —— EXIST PIPE ——
MANHOLE (CABLE IN PVC CONDUIT)		CULVERT		>		12CT FOC12CT FOC	-12CT FOC
		COLVENT			,	24CT MICRO ——24CT MICRO	-24CT MICRO————————————————————————————————————
MANHOLE (CABLE IN BSP/GSP CONDUIT)		BOX CULVERT			<b>,</b>	48CT MICRO 48CT MICRO	-48CT MICRO
H-FRAME	Н	OUTY COUNTY OF STATE FOUND	ID A DVALING			72CT MICRO — 72CT MICRO — 96CT	-72CT MICRO
BORE PIT		CITY, COUNTY OR STATE BOUN	IDARY LINE		<del>-</del>		144CT MICRO———144CT MICRO———
LIGHTNING ARRESTOR	D LIGHTNING ARRESTOR	R.R. CROSSING SIGNAL	<u> 6</u> 02 602	PUSH BRACE	30'-5-84 PB	288CT MICRO ——288CT MICRO——	288CT MICRO 288CT MICRO
AC/DC FILTER PROTECTION	AC/DC FILTER PROTECTION			JOINT USE POLE		24CT MICRO/T24CT MICRO-T	24CT MICRO-T
AOIDO HETERTROTEOTION	PROTECTION	R.R. SIGNAL ARM		JOINT USE POLE	$\otimes$	48CT MICRO/T48CT MICRO-T	48CT MICRO-T——48CT MICRO-T—
ALUMINUM HUB STYLE MARKER	Î	U/G TRANSFORMER		TELEPHONE POLE	$\circ$		72CT MICRO-T72CT MICRO-T
STEEL MARKER	<b>+</b>	OTDEET/OLONAL LIQUE		CONCRETE DOLE			96CT MICRO-T
OTELE MANUELL		STREET/SIGNAL LIGHT	0	CONCRETE POLE	ⓒ		288CT MICRO-T——288CT MICRO-T—
FLAT COMPOSOLITE MARKER	1	PARKING METER	$\triangle$	STEEL POLE	<b>S</b>	RIGHT OF WAY	
TUBULAR MARKER	<b>†</b>	STEEL/WOOD POST	0	POWER POLE	X	DRIVEWAY —	
	•	Olovi	-1				
RIGHT-OF-WAY MARKER	$\bigcirc$	SIGN	q	TRANSFORMER POLE	$\boxtimes$	EDGE OF PAVEMENT — CENTERLINE OF ROAD	
DIQUIT OF WAY DIN		FENCE LINE				DROPS TO HOUSES — — — —	
RIGHT-OF-WAY PIN		TELEPHONE/CATV PED		GROUND WIRE	<u> </u>		
MILE POST MARKER	15 15	TREE			<u>-</u>	AERIAL IMAGES	
NOTE: DASHED = (NOT FOUND IN FIELD)		DUOL	*	BOND AND GROUND	B&G	PROPERTY LINE PL	PL————————————————————————————————————
		BUSH	*		. 545	UTILITY EASEMENT —	

ALL CABLE WILL BE PLACED BY METHOD OF DIRECTIONAL BORE MIN 2' OFF ROW OR EASEMENT @ 42" DOC UNLESS OTHERWISE NOTED.

NOTIFY ALL UTILITIES 72 HOURS PRIOR TO CONSTRUCTION ACTIVITY. ONE CALL SYSTEM @ 1-800-227-6477

# JOB DESCRIPTION PROJECT NAME

PROJECT NAME	PROJECT NAME			
GLEN	WILD 3			
PROJECT CITY				
CAN	ITON			
SHEET	DESCRIPTION			
LEGEND	CONSTRUCTION			
SCALE	DRAWN BY			
NTS	DELTA FIBER			

#### MATERIALS LIST

ITEM	DESCRIPTION	QTY
1	MINI OTE 2 PORT	
2	MINI OTE 4 PORT MINI OTE 8 PORT	
<u>3</u> 4	12 CT FOC	
5	12 CT FOC LOOP	
6	12 CT FOC TAIL	
7	24 CT MICRO	
8	24 CT MICRO LOOP	
9	24 CT MICRO TAIL	
10	48 CT MICRO	
11	48 CT MICRO LOOP	
12	48 CT MICRO TAIL	
13	72 CT MICRO	
14	72 CT MICRO LOOP	
	72 CT MICRO LOOP	
15		
16	96 CT MICRO	
17	96 CT MICRO LOOP	
18	96 CT MICRO TAIL	
19	144 CT MICRO	
20	144 CT MICRO LOOP	
21	144 CT MICRO TAIL	
22	144 CT MICRO FEEDER	
23	144CT M/FEEDER LOOP	
24	144CT M/FEEDER TAIL	
25	288 CT MICRO	
26	288 CT MICRO LOOP	
27	288 CT MICRO TAIL	
28	288 CT MICRO FEEDER	
29	288 CT M/FEEDER LOOP	
30	288 CT M/FEEDER TAIL	
31	BDO144P LCP	
32	BDO288P LCP	
33	BDO432P LCP	
34	BDO576P LCP	
35	FLOWER POT	
36	UH2.5	
37	UH2.5 W/22k LID	
38		
39	UH3 UH4	
40	UH4 UH5	
41	1-1.00" SDR11 HDPE	
41		
	2-1.00" SDR11 HDPE	
43	3-1.00" SDR11 HDPE	
44	1-18/14-2 WAY	
45	1-18/14-4 WAY	
46	EXISTING PIPE	
47	TYCO "A" SPLICE CASE	
48	TYCO "B" SPLICE CASE	
49	TYCO "D" SPLICE CASE	
50	GROUND ROD	
51	OTE SPLICES	
52	NON-OTE SPLICES	
	BM53FA	

MAP NUMBER






DISCLAIMER

EXCEPT AS MAY BE OTHERWISE PROVIDED BY CONTINCT. THESE DOWNINGS AND SPECIFICATIONS SHALL RESULT SISSUED IN STRICT.
COMPEDIES AND SHALL DOT BE REPRODUCED.
COPPEDIES AND SHALL DOTS BERFROQUED.
COPPEDIES AND SHALL DOTS BERFROQUED.
WITHOUT SPECIFIC WITHOUT SPECIFIC SHALL PREMISSION.



MADISON COUNTY, MISSISSIPPI



### **CONSTRUCTION SIGNS**

#### FLUORESCENT ORANGE SHEETING SHALL BE USED ON ALL CONSTRUCTION AND TRAFFIC CONTROL SIGNS







NOTE:
W20-1 SIGNS ARE REQUIRED
WHEN SHOULDER WORK IS
PERFORMED WITH MINOR
ENCROACHMENT TO TRAVEL
LANE OR FLAGGING
OPERATIONS. SEE TCP-2,
FIGURE 6H-6.

DISTANCE BETWEEN SIGNS						
ROAD TYPE	А	В	С			
URBAN (35 MPH OR LESS)	100 FT.	100 FT.	100 FT.			
URBAN (40 - 70 MPH)	350 FT.	350 FT.	350 FT.			
RURAL	500 FT.	500 FT.	500 FT.			
EXPRESSWAY / FREEWAY	1000 FT.	1500 FT.	2640 FT.			

#### NOTES:

- 1. ALL TRAFFIC CONTROL DEVICES ON THIS PROJECT SHALL COMPLY WITH PART VI OF THE MUTCD (LATEST EDITION).
- 2. SIGNS ARE ONLY REQUIRED WHILE CONTRACTOR IS WORKING. THEY SHALL BE INSTALLED PRIOR TO WORK COMMENCING EACH DAY AND REMOVED WHEN WORK IS COMPLETED AT THE END OF THE DAY.
- 3. SIGNS MAY BE MOUNTED ON TRIPODS. THE LOCATION AND SPACING OF SIGNS, AS SHOWN ON THESE TRAFFIC CONTROL PLANS, ARE APPROXIMATE AND MAY BE ADJUSTED AS NECESSARY TO FIT FIELD CONDITIONS.
- 4. CHANNELIZING DEVICES ARE NOT SHOWN ON THIS PLAN, BUT ARE REQUIRED AROUND ACTIVE WORK ZONES (SEE TCP-2).

#### WORK ON SHOULDERS

#### GUIDANCE:

 A SHOULDER WORK sign should be placed on the left side of the roadway for a divided or one-way street only if the left shoulder is affected.

#### OPTION:

- 2. The workers symbol signs may be used instead of SHOULDER WORK signs.
- 3. The SHOULDER WORK AHEAD sign on an intersecting roadway may be omitted where drivers emerging from that roadway will encounter another advance warning sign prior to this activity area.
- 4. For short-duration operations of 60 minutes or less, all signs and channelizing devices may be eliminated if a vehicle with activated rotating lights or strobe lights is used.
- 5. Vehicle hazard warning signals may be used to supplement rotating lights or strobe lights.

#### STANDARD:

- 6. Vehicle hazard warning signals shall not be used instead of the vehicle's rotating lights or strobe lights.
- 7. When paved shoulders having a width of 2.4 m (8ft) or more are closed, at least one advance warning sign shall be used. In addition, channelizing devices shall be used to close the shoulder in advance to delineate the beginning of the work space and direct vehicular traffic to remain within the traveled way.

#### SHOULDER WORK WITH MINOR ENCROACHMENT

#### GUIDANCE:

- 1. All lanes should be a minimum of 3 m (10ft) in width as measured to the near face of the channelizing devices.
- The treatment shown should be used on a minor road having low speeds. For higher-speed traffic conditions, a lane closure should be used.

#### OPTION:

- For short-term use on low-volume, low-speed roadways with vehicular traffic that does not include longer and wider heavy commercial vehicles, a minimum lane width of 2.7 m (9ft) may be used.
- 4. Where the opposite shoulder is suitable for carrying vehicular traffic and of adequate width, lanes may be shifted by use of closely spaced channelizing devices, provided that the minimum lane width of 3 m (10ft) is maintained.
- 5. Additional advance warning may be appropriate, such as ROAD NARROWS sign.

- 6. Temporary traffic barriers may be used along with the work space.
- 7. The shadow vehicle may be omitted if a taper and channelizing devices are used.
- 8. A truck-mounted attenuator may be used on the shadow vehicle.
- For short-duration work, the taper and channelizing devices may be omitted if a shadow vehicle with activated rotating lights or strobe lights is used.
- $10.\ Vehicle\ hazard\ warning\ signals\ may\ be\ used\ to\ supplement\ rotating\ lights\ or\ strobe\ lights.$

#### STANDARD:

11. Vehicle hazard warning signals shall not be used instead of the vehicle's rotating lights or strobe lights. PROJECT NAME
GLENWILD 3


PROJECT CITY
CANTON
SHEET
TC1
DESCRIPTION
TRAFFIC CONTROL
DRAWN BY
DELTA FIBER

MATERIALS LIST

ITEM
DESCRIPTION
QTY.

JOB DESCRIPTION


١			MATERIALS LIS	T
١		ITEM	DESCRIPTION	QTY.
- 1	ı	1	MINI OTE 2 PORT	
- 1	ı	2	MINI OTE 4 PORT	
- 1	ı	3	MINI OTE 8 PORT	
- 1	ı	4	12 CT FOC	
- 1	ı	5	12 CT FOC LOOP	
- 1	ı	6	12 CT FOC TAIL	
- 1	ı	7	24 CT MICRO	
- 1	ı	8	24 CT MICRO LOOP	
- 1	ı	9	24 CT MICRO TAIL	
- 1	ı	10	48 CT MICRO	
- 1	ı	11	48 CT MICRO LOOP	
- 1	ı	12	48 CT MICRO TAIL	
- 1	ı	13	72 CT MICRO	
- 1	ı	14	72 CT MICRO LOOP	
- 1	ı	15	72 CT MICRO TAIL	
- 1	ı	16	96 CT MICRO	
- 1	ı	17	96 CT MICRO LOOP	
- 1	ı	18	96 CT MICRO TAIL	
- 1	ı	19	144 CT MICRO	
- 1	ı	20	144 CT MICRO LOOP	
- 1	ı	21	144 CT MICRO TAIL	
- 1	ı	22	144 CT MICRO FEEDER	
- 1	ı	23	144CT M/FEEDER LOOP	
- 1	ı	24	144CT M/FEEDER TAIL	
- 1	ı	25	288 CT MICRO	
- 1	ı	26	288 CT MICRO LOOP	
- 1	ı	27	288 CT MICRO TAIL	
- 1	ı	28	288 CT MICRO FEEDER	
- 1	ı	29	288 CT M/FEEDER LOOP	
, I	ı	30	288 CT M/FEEDER TAIL	
Ί.	ı	31	BDO144P LCP	
- 1	ı	32		
- 1	ı		BDO288P LCP	
- 1	ı	33	BDO432P LCP	
- 1	ı	34	BDO576P LCP	
- 1	ı	35	FLOWER POT	
- 1	ı	36	UH2.5	
_	ı	37	UH2.5 W/22k LID	
- 1	ı	38	UH3	
- 1	ı	39	UH4	
- 1	ı	40	UH5	
- 1	ı	41	1-1.00" SDR11 HDPE	
- 1	ı	42	2-1.00" SDR11 HDPE	
- 1	ı	43	3-1.00" SDR11 HDPE	
- 1	ı	44	1-18/14-2 WAY	
- 1	ı	45	1-18/14-4 WAY	
- 1	ł	46	EXISTING PIPE	
J	1	47	TYCO "A" SPLICE CASE	
J	1	48	TYCO "B" SPLICE CASE	
- 1	1	49	TYCO "D" SPLICE CASE	
- 1	1	50	GROUND ROD	
- 1	1	51	OTE SPLICES	
- 1	1	52	NON-OTE SPLICES	
J	1	53	BM53FA	
ı	ĺſ		MAP NUMBER	
J				
J	F	·······		<u></u>
- 1	1			



NOTIFY ALL UTILITIES 72 HOURS PRIOR TO CONSTRUCTION ACTIVITY. ONE CALL SYSTEM @ 1-800-227-6477



MADISON COUNTY, MISSISSIPPI



#### **GENERAL NOTES:**

1. THE LOCATION OF CHANNELIZING DEVICES AND THE WORK AREA LAYOUT SHALL BE BASED ON THE CRITERIA IN THE FOLLOWING TABLE. FLAGGER STATIONS SHALL BE LOCATED SUCH THAT APPROACHING VEHICLES WILL HAVE SUFFICIENT DISTANCE TO STOP. VALUES IN STOPPING SIGHT DISTANCE COLUMN MAY BE USED AS A MINIMUM FOR THIS DISTANCE.

POSTED SPEED AND/OR DESIGN SPEED	CH	AXIMUM ANNELIZING CE SPACING (ft)	LONGITUDINAL BUFFER SPACE	STOPPING SIGHT	
mph	TAPER	ALONG LANE LINE & WORK ZONE	(ft)	DISTANCE	
25	20	50	55	155	
30	20	60	85	200	
35	20	70	120	250	
40	20	80	170	305	
45	20	90	220	360	
50	20	100	280	425	
55	20	110	335	495	
60	20	120	415	570	
65	20	130	485	645	

NOTE: BUFFER SPACE MAY BE ADJUSTED AS NEEDED ACCORDING TO ROADWAY GEOMETRY TO MEET SIGHT DISTANCE REQUIREMENTS, AS DIRECTED BY THE ENGINEER.

- 2. ALL CHANNELIZING DEVICES SHALL BE A MINIMUM OF 28" IN HEIGHT.
- 3. DIAMOND SHAPED TRAFFIC CONTROL SIGNS SHALL BE A MINIMUM OF 36" x 36" AND BLACK COPY ON FLUORESCENT ORANGE SHEETING.
- 4. WHEN WORK ZONE IS NO LONGER NEEDED, ALL SIGNS SHALL BE COVERED OR REMOVED AND ALL CHANNELIZING DEVICES SHALL BE MOVED TO THE SHOULDER EDGE.
- 5. ADDITIONAL FLAGGERS MAY BE NEEDED AS DIRECTED BY THE ENGINEER.
- 6. WHEN WORK IS REQUIRED AT NIGHT, FLAGGER STATIONS SHALL BE ILLUMINATED.
- 7. CHANNELIZING DEVICE TYPES FOR:
  A. APPROACH AND EXIT TAPERS RETROREFLECTIVE PLASTIC DRUMS
  B. ALONG LANE LINE AND WORK ZONE TRAFFIC CONES (28" HEIGHT)
- 8. ALL TRAFFIC CONTROL ITEMS SHOWN ON THIS SHEET WILL NOT BE MEASURED FOR SEPARATE PAYMENT. THIS WORK SHALL BE INCLUDED IN THE PRICE BID FOR MAINTENANCE OF TRAFFIC.

### JOB DESCRIPTION

PROJECT NAME
GLENWILD 3

PROJECT CITY
CANTON
SHEET DESCRIPTION
TC2 TRAFFIC CONTROL
SCALE DRAWN BY
DELTA FIBER


		MATERIALS LIS	T
	ITEM	DESCRIPTION	QTY.
	1	MINI OTE 2 PORT	
	2	MINI OTE 4 PORT	
	3	MINI OTE 8 PORT	
	4	12 CT FOC	
	5	12 CT FOC LOOP	
	6	12 CT FOC TAIL	
	7	24 CT MICRO	
	8	24 CT MICRO LOOP	
	9	24 CT MICRO TAIL	
	10	48 CT MICRO	
	11	48 CT MICRO LOOP	
	12	48 CT MICRO TAIL	
	13	72 CT MICRO	
	14	72 CT MICRO LOOP	
	15	72 CT MICRO TAIL	
	16	96 CT MICRO	
	17	96 CT MICRO LOOP	
	18	96 CT MICRO TAIL	
	19	144 CT MICRO	
	20	144 CT MICRO LOOP	
	21	144 CT MICRO TAIL	
	22	144 CT MICRO FEEDER	
	23	144CT M/FEEDER LOOP	
	24	144CT M/FEEDER TAIL	
	25	288 CT MICRO	
	26	288 CT MICRO LOOP	
	27	288 CT MICRO TAIL	
	28	288 CT MICRO FEEDER	
1	29	288 CT M/FEEDER LOOP	
	30	288 CT M/FEEDER TAIL	
	32	BDO144P LCP BDO288P LCP	
		BDO288P LCP BDO432P LCP	
	33	BDO576P LCP	
	35	FLOWER POT	
	36	UH2.5	
	37		
	38	UH2.5 W/22k LID UH3	
	39	UH4	
	40	UH5	
	41	1-1.00" SDR11 HDPE	
	42	2-1.00" SDR11 HDPE	
	43	3-1.00" SDR11 HDPE	
	44	1-18/14-2 WAY	
	45	1-18/14-4 WAY	
	46	EXISTING PIPE	
	47	TYCO "A" SPLICE CASE	
	48	TYCO "B" SPLICE CASE	
	49	TYCO "D" SPLICE CASE	
	50	GROUND ROD	
	51	OTE SPLICES	
	52	NON-OTE SPLICES	
	53	BM53FA	
		MAP NUMBER	





DISCLAIMER

EXCEPT AS MAY BE OTHERWISE PROVIDED ONLY THESE DRAWNINGS AND SPECIFICATION OF THE SEASON OF THE SEASON



001

JOB DESCRIPTION

PROJECT NAME GLENWILD 3 PROJECT CITY CANTON DESCRIPTION CONSTRUCTION SHEET

#### MATERIALS LIST


DRAWN BY DELTA FIBER

		MATERIALS LIS	) I
	ITEM	DESCRIPTION	QTY.
	1	MINI OTE 2 PORT	
	2	MINI OTE 4 PORT	
	3	MINI OTE 8 PORT	
	4	12 CT FOC	376
	5	12 CT FOC LOOP	
	6	12 CT FOC TAIL	50
	7	24 CT MICRO	
	8	24 CT MICRO LOOP	
	9	24 CT MICRO TAIL	
	10	48 CT MICRO	376
	11	48 CT MICRO LOOP	
	12	48 CT MICRO TAIL	50
	13	72 CT MICRO	
	14	72 CT MICRO LOOP	
	15	72 CT MICRO TAIL	
	16	96 CT MICRO	
	17	96 CT MICRO LOOP	
	18	96 CT MICRO TAIL	
	19	144 CT MICRO	376
	20	144 CT MICRO LOOP	
	21	144 CT MICRO TAIL	50
	22	144 CT MICRO FEEDER	
	23	144CT M/FEEDER LOOP	
	24	144CT M/FEEDER TAIL	
	25	288 CT MICRO	
	26	288 CT MICRO LOOP	
	27	288 CT MICRO TAIL	
	28	288 CT MICRO FEEDER	
	29	288 CT M/FEEDER LOOP	
	30	288 CT M/FEEDER TAIL	
	31	BDO144P LCP	
	32	BDO288P LCP	
	33	BDO432P LCP	
	34	BDO576P LCP	
	35	FLOWER POT	
	36	UH2.5	
	37	UH2.5 W/22k LID	
	38	UH3	
	39	UH4	
	40	UH5	
	41	1-1.00" SDR11 HDPE	
	42	2-1.00" SDR11 HDPE	
	43	3-1.00" SDR11 HDPE	
	44	1-18/14-2 WAY	
	45	1-18/14-2 WAY	376
	46		3/0
	-	EXISTING PIPE	
	47	TYCO "A" SPLICE CASE	
	48	TYCO "B" SPLICE CASE	
	49	TYCO "D" SPLICE CASE	
	50	GROUND ROD	
	51	OTE SPLICES	
	52	NON-OTE SPLICES	164
	53	BM53FA	
Ī		MAP NUMBER	

MAP NUMBER







PROJECT NAME GLENWILD 3 PROJECT CITY CANTON


DESCRIPTION CONSTRUCTION SHEET DRAWN BY DELTA FIBER 1"=50"

#### MATERIALCLICE

	MATERIALS LIS	ST.
ITEM	DESCRIPTION	QTY.
1	MINI OTE 2 PORT	5
2	MINI OTE 4 PORT	
3	MINI OTE 8 PORT	
4	12 CT FOC	756
5	12 CT FOC LOOP	240
6	12 CT FOC TAIL	
7	24 CT MICRO	
8	24 CT MICRO LOOP	
9	24 CT MICRO TAIL	
10	48 CT MICRO	752
11	48 CT MICRO LOOP	60
12	48 CT MICRO TAIL	
13	72 CT MICRO	
14	72 CT MICRO LOOP	
15	72 CT MICRO TAIL	
16	96 CT MICRO	
17	96 CT MICRO LOOP	
18	96 CT MICRO TAIL	
19	144 CT MICRO	756
20	144 CT MICRO LOOP	700
21	144 CT MICRO TAIL	
22	144 CT MICRO FEEDER	
23	144CT M/FEEDER LOOP	
24		
25	144CT M/FEEDER TAIL 288 CT MICRO	
26		
	288 CT MICRO LOOP	
27	288 CT MICRO TAIL	
28	288 CT MICRO FEEDER	
29	288 CT M/FEEDER LOOP	
30	288 CT M/FEEDER TAIL	
31	BDO144P LCP	
32	BDO288P LCP	
33	BDO432P LCP	
34	BDO576P LCP	
35	FLOWER POT	1
36	UH2.5	5
37	UH2.5 W/22k LID	
38	UH3	
39	UH4	
40	UH5	
41	1-1.00" SDR11 HDPE	298
42	2-1.00" SDR11 HDPE	
43	3-1.00" SDR11 HDPE	
44	1-18/14-2 WAY	151
45	1-18/14-4 WAY	605
46	EXISTING PIPE	000
47		
48	TYCO "A" SPLICE CASE TYCO "B" SPLICE CASE	
49	TYCO "B" SPLICE CASE	
50		
	GROUND ROD	
51	OTE SPLICES	10
52	NON-OTE SPLICES	
53	BM53FA	
	MAP NUMBER	
	7	







PROJECT NAME GLENWILD 3

PROJECT CITY CANTON

DESCRIPTION CONSTRUCTION SHEET DRAWN BY DELTA FIBER 1"=50"

	MATERIALS LIS	ST.
ITEM	DESCRIPTION	QTY.
1	MINI OTE 2 PORT	4
2	MINI OTE 4 PORT	2
3	MINI OTE 8 PORT	
4	12 CT FOC	367
5	12 CT FOC LOOP	120
6	12 CT FOC TAIL	60
7	24 CT MICRO	
8	24 CT MICRO LOOP	
9	24 CT MICRO TAIL	
10	48 CT MICRO	453
11	48 CT MICRO LOOP	180
12	48 CT MICRO TAIL	
13	72 CT MICRO	
14	72 CT MICRO LOOP	
15	72 CT MICRO TAIL	
16	96 CT MICRO	
17	96 CT MICRO LOOP	
18	96 CT MICRO LOOP	
19	144 CT MICRO	
20	144 CT MICRO LOOP	
21	144 CT MICRO TAIL	
22	144 CT MICRO FEEDER	
23	144CT M/FEEDER LOOP	
24	144CT M/FEEDER TAIL	
25	288 CT MICRO	
26	288 CT MICRO LOOP	
27	288 CT MICRO TAIL	
28	288 CT MICRO FEEDER	
29	288 CT M/FEEDER LOOP	
30	288 CT M/FEEDER TAIL	
31	BDO144P LCP	
32	BDO288P LCP	
33	BDO432P LCP	
34	BDO576P LCP	
35		
	FLOWER POT	_
36	UH2.5	6
37	UH2.5 W/22k LID	
38	UH3	
39	UH4	
40	UH5	
41	1-1.00" SDR11 HDPE	820
42	2-1.00" SDR11 HDPE	
43	3-1.00" SDR11 HDPE	
44	1-18/14-2 WAY	
45	1-18/14-4 WAY	
46	EXISTING PIPE	
47		
48	TYCO "A" SPLICE CASE	
	TYCO "B" SPLICE CASE	
49	TYCO "D" SPLICE CASE	
50	GROUND ROD	1
51	OTE SPLICES	26
52	NON-OTE SPLICES	
53	BM53FA	1
	MAP NUMBER	
s	8 ::::	

4


PREPARED BY

ONE CALL SYSTEM @ 205-731-3200



DISCLAIMER

007



PROJECT NAME GLENWILD 3 PROJECT CITY CANTON DESCRIPTION CONSTRUCTION SHEET DRAWN BY DELTA FIBER

1"=50'


	MATERIALS LIS	ST.
ITEM	DESCRIPTION	QTY.
1	MINI OTE 2 PORT	2
2	MINI OTE 4 PORT	1
3	MINI OTE 8 PORT	
4	12 CT FOC	
5	12 CT FOC LOOP	
6	12 CT FOC TAIL	
7	24 CT MICRO	
8	24 CT MICRO LOOP	
9	24 CT MICRO TAIL	
10	48 CT MICRO	453
11	48 CT MICRO LOOP	180
12	48 CT MICRO TAIL	
13	72 CT MICRO	
14	72 CT MICRO LOOP	
15	72 CT MICRO TAIL	
16	96 CT MICRO	
17	96 CT MICRO LOOP	
18	96 CT MICRO TAIL	
19		
	144 CT MICRO	
20	144 CT MICRO LOOP	
21	144 CT MICRO TAIL	
22	144 CT MICRO FEEDER	
23	144CT M/FEEDER LOOP	
24	144CT M/FEEDER TAIL	
25	288 CT MICRO	
26	288 CT MICRO LOOP	
27	288 CT MICRO TAIL	
28	288 CT MICRO FEEDER	
29	288 CT M/FEEDER LOOP	
30	288 CT M/FEEDER TAIL	
31	BDO144P LCP	
32	BDO288P LCP	
33	BDO432P LCP	
34	BDO576P LCP	
35	FLOWER POT	2
36	UH2.5	3
37		3
	UH2.5 W/22k LID	
38	UH3	
39	UH4	
40	UH5	
41	1-1.00" SDR11 HDPE	668
42	2-1.00" SDR11 HDPE	
43	3-1.00" SDR11 HDPE	
44	1-18/14-2 WAY	
45	1-18/14-4 WAY	
46	EXISTING PIPE	
47	TYCO "A" SPLICE CASE	
48	TYCO "B" SPLICE CASE	
49	TYCO "D" SPLICE CASE	
50	GROUND ROD	
51	OTE SPLICES	0
52		8
	NON-OTE SPLICES	
53	BM53FA	
	MAP NUMBER	
	9	





DISCLAIMER

ONE CALL SYSTEM @ 205-731-3200



PROJECT NAME

GLENWILD 3

PROJECT CITY

 CANTON

 SHEET
 DESCRIPTION CONSTRUCTION

 SCALE
 DRAWN BY

 1"=50'
 DELTA FIBER

#### MATERIALS LIST

	MATERIALS LIST		
ITEM	DESCRIPTION	QTY.	
1	MINI OTE 2 PORT	3	
2	MINI OTE 4 PORT		
3	MINI OTE 8 PORT	1	
4	12 CT FOC	88	
5	12 CT FOC LOOP		
6	12 CT FOC TAIL	60	
7	24 CT MICRO		
8	24 CT MICRO LOOP		
9	24 CT MICRO TAIL		
10	48 CT MICRO	453	
11	48 CT MICRO LOOP	180	
12	48 CT MICRO TAIL		
13	72 CT MICRO		
14	72 CT MICRO LOOP		
15	72 CT MICRO TAIL		
16	96 CT MICRO		
17	96 CT MICRO LOOP		
18	96 CT MICRO TAIL		
19	144 CT MICRO		
20	144 CT MICRO LOOP		
21	144 CT MICRO TAIL		
22			
	144 CT MICRO FEEDER		
23	144CT M/FEEDER LOOP		
24	144CT M/FEEDER TAIL		
25	288 CT MICRO		
26	288 CT MICRO LOOP		
27	288 CT MICRO TAIL		
28	288 CT MICRO FEEDER		
29	288 CT M/FEEDER LOOP		
30	288 CT M/FEEDER TAIL		
31	BDO144P LCP		
32	BDO288P LCP		
33	BDO432P LCP		
34	BDO576P LCP		
35	FLOWER POT	2	
36	UH2.5	4	
37	UH2.5 W/22k LID		
38	UH3		
39	UH4		
40	UH5		
41	1-1.00" SDR11 HDPE	843	
41	2-1.00" SDR11 HDPE	043	
42	3-1.00" SDR11 HDPE		
44	1-18/14-2 WAY		
45	1-18/14-4 WAY		
46	EXISTING PIPE		
47	TYCO "A" SPLICE CASE		
48	TYCO "B" SPLICE CASE		
49	TYCO "D" SPLICE CASE		
50	GROUND ROD	1	
50	075 081 1050	17	
51	OTE SPLICES	17	
	NON-OTE SPLICES	- 17	
51		1	




ONE CALL SYSTEM @ 205-731-3200



DISCLAIMER

EXCEPT AS MAY BE OTHERWISE PROVIDED BY OWNTHON.'T INVEST DRAWNINGS AND SPECIFICATIONS SHALL BEAM SHALL BE BEAM SISSED IN STITL CONFEDENCE AND SHALL NOT BE REPORTED. COMPEDIAC AND ANALL NOT BE REPORTED. COMPEDIA OR USED FOR ANY PURPOSE WITHOUT SPECIFIC WRITTEN PERMISSION.



PROJECT NAME GLENWILD 3

PROJECT CITY CANTON

DESCRIPTION CONSTRUCTION SHEET DRAWN BY DELTA FIBER

#### MATERIALS LIST

	MATERIALS LIS	5 I
ITEM	DESCRIPTION	QTY.
1	MINI OTE 2 PORT	3
2	MINI OTE 4 PORT	
3	MINI OTE 8 PORT	1
4	12 CT FOC	
5	12 CT FOC LOOP	
6	12 CT FOC TAIL	
7	24 CT MICRO	
8	24 CT MICRO LOOP	
9	24 CT MICRO TAIL	
10	48 CT MICRO	368
11	48 CT MICRO LOOP	180
12	48 CT MICRO TAIL	30
13	72 CT MICRO	
14	72 CT MICRO LOOP	
15	72 CT MICRO TAIL	
16	96 CT MICRO	
17	96 CT MICRO LOOP	
18	96 CT MICRO TAIL	
19	144 CT MICRO	
20	144 CT MICRO LOOP	
21	144 CT MICRO TAIL	
22	144 CT MICRO FEEDER	
23	144CT M/FEEDER LOOP	
24	144CT M/FEEDER TAIL	
25	288 CT MICRO	
26	288 CT MICRO LOOP	
27	288 CT MICRO TAIL	
28	288 CT MICRO FEEDER	
29	288 CT M/FEEDER LOOP	
30	288 CT M/FEEDER TAIL	
31	BDO144P LCP	
32	BDO288P LCP	
33	BDO432P LCP	
34	BDO576P LCP	
35	FLOWER POT	2
36		4
37	UH2.5	4
_	UH2.5 W/22k LID	
38	UH3	
39	UH4	
40	UH5	
41	1-1.00" SDR11 HDPE	571
42	2-1.00" SDR11 HDPE	
43	3-1.00" SDR11 HDPE	
44	1-18/14-2 WAY	
45	1-18/14-4 WAY	
46	EXISTING PIPE	
47	TYCO "A" SPLICE CASE	
48	TYCO "B" SPLICE CASE	
49	TYCO "D" SPLICE CASE	
50	GROUND ROD	1
51	OTE SPLICES	11
52	NON-OTE SPLICES	
	BM53FA	1
53	IDIVIDOFA	



